

BOLIX BQS

Elastic Brick Slips

PRODUCT DESCRIPTION:

- High flexibility and resistance to thermal stress
- High resistance to:
 - precipitation, frost and hail,
 - UV radiation - contains UV absorbers
 - algal and fungal growth
 - impact and scratch
 - dirt build-up
- water vapour permeable
- Frost resistant
- Easy and fast to install and work
- Minimised material losses during cutting
- After fixing the facing does not need to be treated with a sealer to reduce water penetration
- Perfectly imitates the appearance of a traditional brick masonry wall
- Light weight - total weight of adhesive/joint filler and the cladding is around 7 kg/m²

USE:

BOLIX BQS elastic brick slips provide a decorative finish that perfectly imitates brick masonry wall. The decorative slips may be fixed to exterior walls of existing and new buildings with or without EWI as well as in interiors.

Suitable surface for BOLIX BQS brick slips:

- base coat of External Wall Insulation Systems (EWI) with EPS boards or mineral wool batts,
- concrete,
- cement, cement-lime or gypsum plasters,
- plasterboard, cement board, fibre-cement board, cement particle board firmly fixed to the substrate
- mineral repair mortar, base coat/adhesive
- resurfacers, skim coats

SURFACE PREPARATION:

Reinforced Base Coat

The current EWI Instruction Manual IB/01 EPS (system with EPS boards) or IB/02 MW (system with mineral wool batts) must be followed when applying EWI and the reinforced base coat in particular.

Mineral substrates, not insulated

The surface must be structurally sound, stable, even, clean of surface contaminants such as dust, grease, bitumen and other barrier materials that may affect adhesion. Remove old paint coats, loose, peeling or flaking plaster. Prime porous surface (particularly aerated concrete) with the primer BOLIX N. Even out minor irregularities with a base coat for embedding reinforcing mesh such as BOLIX U. Level major gaps and imperfections with the mortar BOLIX W and when set, smooth out the entire surface with the above base coat or joint compound.

For gypsum plaster, plasterboards, gypsum and polymer skim coats, prime the surface with the primer BOLIX Ultragrunt and when it has dried, apply BOLIX OP.

Each surface to which flexible bricks will be attached must be first primed with the undercoat BOLIX OP.

PRODUCT PREPARATION:

A ready-made product. Product properties are provided in the paragraph TECHNICAL DATA.

To reduce waste, plan the layout of the brick slips across one individual surface prior to the installation. It is advisable to start with measuring and marking out on the surface the top horizontal line and the vertical lines (head joints) for the first few brick slips. Plan for the joint width. Use a spirit level or builders string to plan and mark brick courses.

APPLICATION:

Spread the ready mix adhesive and grout SOLTHERM BQB across the surface using a 4x4 notched trowel or putty knife. Finally, work perpendicular to the long edge of the attached flexible brick slips. Apply the product in one operation to a surface area to make sure it will not dry out before attaching the slip (the surface should not exceed 1 m²).

Start tiling from the corner, work top down. For corners, simply bend the brick slips to fit. Priorly, sand any too sharp corners and remove dust. In colder temperatures, the slips should have higher temperature during bending to prevent formation of hairline cracks on them.

Second option is cutting the slips. Butt joint the cut tiles at corners and after initial drying of the adhesive and grout (min. 4h under optimal conditions i.e. +23 °C and 50 % relative air humidity) fill the interstice that has formed between edges of the fixed slips with the paste BOLIX BQS Mass in the colour of the facing, making sure that the joint is weathertight. Joints between brick slips should be undetectable from the distance of a few metres.

Individual brick slips can be cut to the desired size with scissors or cut from the back side with a wallpaper knife and break.

Brick slips should be installed in courses, working from the top down. This technique will help to prevent soiling of the slips laid below.

Install the brick on freshly applied adhesive and apply firm and even pressure to entire face of the elastic brick slip BOLIX BQS. Make sure that the compound is tight around the brick for a good hold. Use spacers in between slips to get a consistent gap and grout lines throughout your installation and make sure that the slip is properly aligned with the previously fixed slips. Check the consistency of the grout lines every few courses.

Lay the slips in a desired and previously planned pattern (staggered, offset) and make sure that the joint width is between 10÷12 mm. When the slips are laid and before the skin develops on the compound surface, go over the joints with a flat and damp (but not wet) paintbrush size matching the joint width to smooth and form them. The joints must be tightly filled to seal and prevent rainwater migration under the brick slips - make sure that the brick slip edges are embedded in the adhesive.

LIMITATIONS AND RECOMMENDATIONS:

- Make sure that the surface is even and well prepared.
- Prior to adhesive application, allow fresh cement and lime-cement plasters to cure for minimum 3-4 weeks and gypsum plasters for minimum 2 weeks.
- Do not apply to areas subject to prolonged water exposure (and to vertical surfaces in particular), accumulated snow and to areas not damp-proofed against capillary action.
- Before the decorative effect is created, cover or mask all adjacent on which the panels are not to be installed.



Masz pytania?

Zadzwoń!
801-650-222

Napisz!
serwis@bolix.pl

BOLIX SA

Ul. Stolarska 8
34-300 Żywiec
Tel. 33 475 06 00
Fax. 33 475 06 12

Znajdź nas

www.trwaleocieplenie.pl
www.facebook.com/bolixsa
www.bolix.pl

BOLIX BQS

Elastic Brick Slips

- Plan the surface area taking into consideration weather conditions, surface type and workforce.
- If a brick slip is placed incorrectly, lift it back up, collect the adhesive mortar, apply fresh BOLIX BQB adhesive/grout compound on the surface and fix a new brick slip. Any damaged brick slips must be disposed of.
- During application operation and for 3 days after completion, protect the surface from direct sunlight exposure, precipitation, wind and temperatures below +5°C. Use scaffolding meshes.
- Care should be taken to avoid brick slips soiling with the material. Clean off any soiling immediately or replace the soiled brick slip.
- As you progress through a project lift random brick slips occasionally (right after they have been installed) to check the BOLIX BQB coverage.
- Low temperature, increased humidity and improper air circulation extend the provided drying time of the adhesive.
- Tile each separate wall surface with brick slips from the same batch. Unless, colour and texture variances are acceptable or even desired. You can also obtain colour variation effect by mixing brick slips from different production batches prior to installation.
- During application and afterwards, ventilate the room, until the characteristic odour disappears.
- Make sure that skinning of the adhesive&grout has not started before installing the facing product, as this may affect and impair the adhesion and lead to bond failure and delamination/debonding of the brick slips. If the skin develops, remove the adhesive and apply fresh material.
- Do not back butter the brick slips, the compound should be applied directly to the surface.
- Clean tools and hands with running water immediately after use. After drying difficulties with cleaning may be experienced.

PRECAUTIONS:

Protect eyes and skin. In case of eye contact, flush eyes with plenty of water and seek medical advice.

TOOLS:

- Agitator or slow-speed drill (400÷500 rpm) with a hoop paddle.
- 4x4 mm toothed trowel or spatula
- Taping knife
- Paintbrush (size to match the joint width)
- Scissors / wallpaper knife
- Builder's square
- Pencil
- Tape measure
- Spirit level / string line / laser
- Jointer trowel/pointing trowel

TECHNICAL DATA:

The following technical data are for the temperature of +23 (±2)°C and relative air humidity of 50 (±5)%. Under other conditions the technical data may vary.

Ambient and surface temperature at application and setting:
from +5°C to +25°C

Relative humidity at application and setting:
up to 80%

Thermal resistance after drying of the adhesive:

From -35°C to +100°C

Colour:

10 colours as in the SOLTHERM reference card:

other colours made to order based on the customer's sample or reference card



WARM COPPER



ORANGE SAND



GINGER ROCK



RED CRISTALE



RUBY STONE



DARK GRANITE



BLACK BASALT



GREY MARBLE



WHITE LABASTER



NATURAL TRAVERTINE

Brick slip width:

240 mm*

Brick slip height:

71 mm*

Brick slip thickness:

3÷5 mm

Brick slip surface:

Smooth, rough, textured (different patterns)

Grain size acc. to EN 1062-1:

< 0,8 mm

Coefficient of heat conductivity λ:

≤ 0.70 W/(m*K)

Vapour transmission rate according to EN 1062:-1 (system composed of the adhesive/grout SOLTHERM BQB and the elastic brick slip SOLTHERM BQS):

≥ 50 g/(m²d)

Category V2 (15-150 g/(m²d))

Water permeability as per PN-EN 1062-1 (system composed of the adhesive/grout SOLTHERM BQB and the elastic brick slip SOLTHERM BQS):

≤ 0.29 kg/(m²h^{0.5})

W2 category (0.1-0.5 kg/(m²h^{0.5}))

Packaging:

box: 144 pcs

No. of containers per pallet and net weight:

maximum 48 boxes (ca. 576 kg) / 1 box ca. 12 kg



Masz pytania?

Zadzwoń!
801-650-222

Napisz!
serwis@bolix.pl

BOLIX SA

Ul. Stolarska 8
34-300 Żywiec
Tel. 33 475 06 00
Fax. 33 475 06 12

Znajdź nas

www.trwaleocieplenie.pl
www.facebook.com/bolixsa
www.bolix.pl

BOLIX BQS

Elastic Brick Slips

Shelf life:

12 months from the date of production provided on the packaging

**Notice: The tiles can also be manufactured in other sizes and shapes as arranged between the manufacturer and the customer.*

APPROXIMATE COVERAGE:

ca. 50 pcs/m² - tile size 240 x 71 mm, joint width 10 mm

ca. 48 pcs/m² - tile size 240 x 71 mm, joint width 12 mm

Coverage may vary with tile size and joint width.

STORAGE:

Store in intact containers in temp. between +5°C and +25°C. Protect from direct sunlight and frost. Store away from the reach of children.

COMPOSITION:

Quartz sand, polymer resins, mineral fillers, iron oxide based pigments, biocides and modifiers.

SOLTHERM guarantees product quality but has no control over its application and use. SOLTHERM takes no responsibility for contractors' and distributors' performance. The information supplied herein is given in good faith based on our current knowledge and latest application methods. The information provided cannot replace designer's and contractor's expertise and does not dismiss anyone from observing good practice and the OHS regulations. Should you have any further queries, carry out necessary tests or contact SOLTHERM Technical Department. The publication of this Technical Data Sheet renders older editions invalid.



Masz pytania?

Zadzwoń!
801-650-222

Napisz!
serwis@bolix.pl

BOLIX SA

Ul. Stolarska 8
34-300 Żywiec
Tel. 33 475 06 00
Fax. 33 475 06 12

Znajdź nas

www.trwaleocieplenie.pl
www.facebook.com/bolixsa
www.bolix.pl